

FIXED SPEED SPLIT AC SERIES

ACE 3200f



| | | | |
|---------------|-----|-----|-----|
| TONNAGE CLASS | 1.0 | 1.5 | 2.0 |
| STAR RATING | | | |

KEY FEATURES



FEATURES

- ⊙ AUTO RESTART
- ⊙ ASYMMETRIC LOWER MOVEMENT
- ⊙ SUPERCool FUNCTION
- ⊙ ON/OFF TIMER WITH ADVANCED START-UP
- ⊙ DIGILOCK
- ⊙ ONE TOUCH SILENT FAN SPEED

TECHNICAL SPECIFICATIONS

ACE 3200f

| DESCRIPTION | UNIT | ACE 3200f | | |
|--------------------------------------|---|-----------------|------------------|------------------|
| TONNAGE CLASS | | 1.0TR | 1.5TR | 2.0TR |
| Star Rating | No of BEE Stars | 3 | 3 | 3 |
| Unit | Model Number | RAU312HWDS | RAU318HWDS | RAU323HWDS |
| IDU | Model Number | RAS312HWDS | RAS318HWDS | RAS323HWDS |
| ODU | Model Number | RAC312HWDS | RAC318HWDS | RAC323HWDS |
| Compressor | Type | ROTARY | ROTARY | ROTARY |
| Rated Power Supply | Volts/Hz/Phase | 230/50/1 | 230/50/1 | 230/50/1 |
| Rated Cooling Capacity | BTU/Hr | 12000 | 18300 | 23960 |
| Rated Cooling Capacity | Watts | 3517 | 5362 | 7020 |
| Rated Power Input | Watts | 1070 | 1630 | 2134 |
| EER | *Rated Cooling Capacity (Watts) / Power Input (Watts) | 3.29 | 3.29 | 3.29 |
| Current Drawn | Amps | 4.8 | 7.3 | 9.5 |
| Fan Speed | Steps | 5 | 5 | 5 |
| Air Flow (IDU) (Cooling -Super High) | CFM | 441 | 583 | 636 |
| Sound Level* (IDU) | dB | 38 | 34 | 37 |
| Dimension (IDU) (W X H X D) | mm | 830 X 290 X 220 | 1050 X 290 X 220 | 1050 X 290 X 220 |
| Dimension (ODU) (W X H X D) | mm | 750 X 548 X 288 | 750 X 548 X 288 | 792 X 600 X 299 |
| Net Weight (IDU) | Kg | 10 | 12.9 | 12.9 |
| Net Weight (ODU) | Kg | 32.4 | 40 | 46.1 |
| Remocon | Type | Wireless | Wireless | Wireless |

Features may vary from model to model, some of the models may not be available at all Hitachi outlets. *At Super silent fan speed & at a distance of 1mtr., Hitachi air-conditioners are designed to work in ambient temperatures upto 52°C. Due to continuous research and development, specifications, features and model colour may change without any prior notice.